


Product data sheet

ECOLINE OFFICE 1500 39W LED 4000K RA>80 CD DP-SM
8246090559
SG ARMATUREN



Box Lean is available with double parabolic louvre and is suitable for schools and office lighting. Low energy consumption. Cost-cutting solution by avoiding the hassle of relamping. Light Distribution Direct Light source LED (3000K/4000K): D: 19W, 33W, 39W D/I: 34W, 39W Ra>80 SDCM: 3 L80/B10 >50.000h at Ta=25°C. Optics Direct: PMMA and satin-matt double parabolic louvre. Materials and finish Housing: Powder coated steel white 25% gloss. Double parabolic louvre in Miro finish. LED cover in PMMA. Control Gear Electronic driver: CD. CD-DA (DALI). Protection Class I, IP20, Ta=25°C, CE. Mounting/Connection Wire suspended or surface mounted. Adjustable wire suspensions to be ordered separately (2x2m). Cable entry on top of luminaire or in end caps. Connection direct in terminal block.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39 W	CRI	80
Total flux	4650 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	39 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 59.06 in

Width: 5.59 in

Height: 2.48 in

Adjustability

Fixed

Electric

System power: 39 W

Appliance Class: I

Protection

IP: 20