Product data sheet

PAULA VI 9.646.2036.05

LEIPZIGER LEUCHTEN









Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	50 W	
Lamp flux	3500 lm	
Luminous efficacy	47 lm/W	
CCT	2000 K	

LOR	83%
Total flux	2909 lm
Total power	62 W



1 x High pressure sodium vapour lamp

1 X Flight pressure social in Vapour lamp			
Nominal lamp power	70 W	LOR	
Lamp flux	5600 lm	Total flux	
Luminous efficacy	56 lm/W	Total power	
CCT	2000 K		
CRI	25		

25

Mounting mode Electric

Pole top mounted System power: 62-83 W

Shape and measurements Protection

CRI

Height: 28.74 in IP: 55

Diameter: 28.74 in Designation labels: CE, F

83% 4654 lm 83 W